






RoHS compliant



Recommended PCB Layout
(Tolerance:±0.05)



1.Material:

1.1 Housing: PBT UL94V-0 Black.

Insert: PBT UL94V-0 Black.

1.2 Shell: 30u" Ni Over Brass(C2680),T=0.20mm.

1.3 RJ45 Terminal:Phosphor Bronze(C5191) T=0.35mm
Plating:6u" Gold Plated On Contact Area,
80u" ~120u" Tin Plated On Solder Area,
50u" ~80u" Ni Underplated Overall.


1.4 Tail Terminal: Brass(C2680) T=0.35mm,
Plating: 80u" ~120u" Tin Plated Over,
30u" ~50u" Ni Underplated Overall.

2.Environmental requirements:

2.1 Lead-free process,compliant RoHS.

					GENERAL TOLERANCE		DRAWN		Gene Li		2019/04/17		X-SHUN 东莞市祥舜电子科技有限公司 DONGGUAN X-SHUN ELECTRONIC TECHNOLOGY CO., LTD					
					.X	±0.35	X.°	± 2°	CHECKE								PART NO.	
A0		NEW DESIGN		2019/04/17		.XX	±0.25	X.°	± 1°	APPROVE				TITLE:		RJ45 TAB-UP 1000BASE-TX 1X1 W/SHIELD		
						.XXX	±0.15	.XX°	± 0.5°									
REV	ECN NO	DESCRIPTION		DATE	SIGNATURE	PROJECT			UNIT	mm	SCALE	1:1	SHEET	1/3	REV	A0	DRAWING NO.	202-G205
																		

RoHS compliant



3. Electrical Specification @25°C:

3.1 Inductance: 350uH Min With 8mA DC bias.

3.2 Insertion loss :
1-100MHZ -1.0dB max.

3.3 Return loss :
1-30MHZ -18dB min.
30-60MHZ -16dB min.
60-80MHZ -12dB min.
80-100MHZ -10dB min.

3.4 Common Mode Rejection: 1-100MHZ -30dB min.

3.5 Cross Talk: 1-100MHZ -30dB min.

4. Operating and Storage Temperature:

4.1 Operating Temperature : -40°C to +85°C.


4.2 Storage Temperature : -40°C to +85°C.

5. Wave soldering peak temperature: 260°C.

					GENERAL TOLERANCE		DRAWN		Gene Li		2019/04/17		X-SHUN 东莞市祥舜电子科技有限公司 DONGGUAN X-SHUN ELECTRONIC TECHNOLOGY CO., LTD				
					.X	±0.35	X.°	± 2°	CHECKE								PART NO.
A0		NEW DESIGN	2019/04/17		.XX	±0.25	.X.°	± 1°	APPROVE				TITLE:		RJ45 TAB-UP 1000BASE-TX 1X1 W/SHIELD		
				.XXX	±0.15	.XX°	± 0.5°	PROJECT									
REV	ECN NO	DESCRIPTION	DATE	SIGNATURE				UNIT	mm	SCALE	1:1	SHEET	2/3	REV	A0	DRAWING NO.	202-G205

RoHS compliant


1



每吸塑盒放120PCS产品

图周用订书针订紧
吸塑盒

2




8吸塑盒为一叠

用拉伸膜“十”字型扎紧

3


每箱放8盒吸塑盒，
(共8盒960PCS产品)



4

封箱胶纸封箱

客户代码



					GENERAL TOLERANCE		DRAWN		Gene Li		2019/04/17		X-SHUN 东莞市祥舜电子科技有限公司 DONGGUAN X-SHUN ELECTRONIC TECHNOLOGY CO., LTD					
					.X	±0.35	X.°	± 2°	CHECKE				PART NO.	20211G-1110-G205				
					.XX	±0.25	.X°	± 1°										
A0		NEW DESIGN	2019/04/17		.XXX	±0.15	.XX°	± 0.5°	APPROVE									
REV	ECN NO	DESCRIPTION	DATE	SIGNATURE	PROJECT			UNIT		mm	SCALE	1:1	SHEET	3/3	REV	A0	DRAWING NO.	202-G205
																		