



RoHS compliant



NOTES

MATERIAL





1. HOUSING MATERIAL : PBT BLACK UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.30mm.
3. PLATING : CONTACT AREA-SELECTIVE GOLD PLATING, TAILS PLATING TIN OVER NICKEL

ELECTRICAL


1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 60 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500V DC .
5. DIELECTRIC RESISTANCE : 1000V AC RMS 60Hz, 1MIN.
6. DURRABILITY : 750 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE : -40°C~+85°C.
2. OPERATION : -20°C~+75°C.



Front Panel Jack Only Clearance
W/O Latch Feature



Single Panel-Latch Clearance
Panel Thickness 1.20mm

6U 5001-ZTS90D-006S
30U 5001-ZTS90D-016S

					GENERAL TOLERANCE		DRAWN		Gene Li		2018/09/12		X-SHUN 东莞市祥舜电子科技有限公司 DONGGUAN X-SHUN ELECTRONIC TECHNOLOGY CO., LTD							
						.X ±0.35	X.° ± 2°	CHECKE		TM			PART NO. SEE TABLE							
A0		NEW DESIGN		2018/09/12		.XX ±0.25	.X.° ± 1°	APPROVE					TITLE: 90° 全塑卡扣直通							
REV	ECN NO	DESCRIPTION		DATE	SIGNATURE	PROJECT		UNIT	mm	SCALE	1:1	SHEET				REV	A0	DRAWING NO.		